

## ELECTRIC ARTICULATING BOOM LIFTS

# AB14EJ (AB460EJ)/AB16EJ (AB520EJ)

Compliant with CE/ANSI/CSA/AS/EAC standards

## PRODUCT HIGHLIGHTS

### Suitable for Working in Narrow Space

- These machines are designed with narrow chassis, lower stowed height enables to pass standard doorways and travel in narrow aisles both indoors and outdoors
- It is easy to get access to up and over with proportional control joysticks

### Easy Maintenance

- One button for trouble shooting by checking a 5 inch LED screen on the ground control, manuals free
- AGM maintenance-free batteries come as standard, long cycle life and no worries of maintenance decreasing TCO

### Electrical Emergency Lowering System

- When the main power system is out of power or fails, it is easy and highly efficient to bring platform lowering to ground from both ground and platform control by using a separate auxiliary power unit



Standard Features		
5 inch LED screen	2WD x 2WS	Electrical emergency lowering system
Proportional control with 2 joysticks	Automotive-grade sleeves for all pipes	Weighing system
Hydraulic platform leveling	Max tilt rating to 5°	Emergency stop system
Horn & buzzer	Footswitch	Fault diagnosis system
Flashing beacon	Manual storage box	Tilt protection system
Foam-filled non-marking tires	1.45m(4'9") platform (AB14EJ) 1.83m(6') platform with swing gate (AB16EJ)	AC power to platform
Secondary guarding device	Telematics-ready connector	
Options & Accessories		
Solid tires	Overhead anti-collision device	Glazier kit
Half mesh	Anti-pinch rail	

**SINOBOOM™**

**PARTNERS IN ACCESS™**

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

# ELECTRIC ARTICULATING BOOM LIFTS AB14EJ (AB460EJ)/AB16EJ (AB520EJ)

Compliant with CE/ANSI/CSA/AS/EAC standards

Model	AB14EJ (AB460EJ)	AB16EJ (AB520EJ)
<b>Dimensions</b>		
Max Platform Height	14 m (45'11")	15.7 m (51'6")
Max Working Height	16 m (52'6")	17.7 m (58'1")
Max Horizontal Outreach	7.6 m (24'11")	9.3 m (30'6")
Max Up and Over Clearance	7.8 m (25'7")	7.8 m (25'7")
A Stowed Length	6 m (19'8")	6.8 m (22'4")
B Overall Width	1.73 m (5'8")	1.9 m (6'3")
C Stowed Height	2 m (6'7")	2 m (6'7")
Stowed Length (Transport)	6 m (19'8")	6.8 m (22'4")
Overall Width (Transport)	1.73 m (5'8")	1.9 m (6'3")
Stowed Height (Transport)	2 m (6'7")	2 m (6'7")
D Wheelbase	1.9 m (6'3")	1.9 m (6'3")
Ground Clearance	0.22 m (8.7")	0.22 m (8.7")
Platform Dimensions(L×W×H)	1.45 m×0.85 m×1.1 m (4'9"×2'9"×3"7")	1.83 m×0.85 m×1.1 m (6'×2'9"×3"7")
<b>Performance</b>		
Max Platform Capacity	230 kg (507 lbs)	230 kg (507 lbs)
Max Platform Occupants	2 Persons	2 Persons
Drive Speed (Stowed)	5.2 km/h (3.2 mph)	5.2 km/h (3.2 mph)
Drive Speed (Raised)	0.8 km/h (0.5 mph)	0.8 km/h (0.5 mph)
Gradeability	30%	30%
Turntable Rotation	355°/Non-continuous	355°/Non-continuous
Platform Rotation	160°	160°
Tilt Rating	5°	5°
Turning Radius (Inside/Outside)	1.15 m/3.51 m (3'9"/11'6")	0.7 m/3.31 m (2'4"/10'10")
Turntable Tail-Swing	0 m	50 mm (2")
Max Allowable Side Force	400 N (90 lbf)	400 N (90 lbf)
Max Allowable Wind Speed	12.5 m/s (28 mph)	12.5 m/s (28 mph)
Tire Spec/Type	240/55D17.5 Foam-filled	240/55D17.5 Foam-filled
<b>Power</b>		
Drive × Steer	2 WD×2 WS	2 WD×2 WS
Batteries	48 V, 390 Ah (AGM batteries)	48 V, 390 Ah (AGM batteries)
Hydraulic Tank Capacity	40L (8.8 gal (UK)/10.6 gal (US))	40L (8.8 gal (UK)/10.6 gal (US))
System Voltage	12 VDC	12 VDC
<b>Weight</b>		
Weight	7,160 kg (15,785 lbs)	7,380 kg (16,270 lbs)
Standards Compliance	CE/ANSI/CSA/AS/EAC	CE/ANSI/CSA/EAC

